

SPECIFICATIONS:

1. Rating: DC 20V 7.5A Max.
2. Contact:resistance:30mΩMax.
3. Insulation Resistance:DC 250V 50MΩMin.
4. Voltage Withstanding:AC 250V 1Minute.
5. INSERTION FORCE:4.5kgf Max.
- WITHDRAWAL FORCE:1.0kgf~4.5kgf Min.



Build of material:

項次	名稱	料號	材質	電鍍或顏色	數量	備註
1	POWER四粗母座外膠殼-上蓋	DP0400110	PBT+15%GF, UL 94 V-0	BLACK	1	
2	POWER四粗母座外膠殼-下蓋	DP0400210	PBT+15%GF, UL 94 V-0	BLACK	1	
3	POWER四粗母座-PIN1	DP0400310	BASS T=0.30±0.03mm	TIN PLATED	1	
4	POWER四粗母座-PIN2	DP0400410	BASS T=0.30±0.03mm	TIN PLATED	1	
5	POWER四粗母座-PIN3	DP0400510	BASS T=0.30±0.03mm	TIN PLATED	1	
6	POWER四粗母座-PIN4	DP0400610	BASS T=0.30±0.03mm	TIN PLATED	1	
7	POWER二粗一細母座-接地銅管	DP0300410	BASS T=0.40±0.03MM	TIN PLATED(霧)	1	共用


東莞世華電子有限公司
 SHYH HWA ELECTRONICS CO.,LTD.(DONGGUAN)
 地址:東莞市塘廈鎮諸佛嶺178工業區
 TEL:0769-7910020-1 FAX:0769-7910210

DRAWN BY 柏艷云
 CHECKED BY
 APPROVED BY

ITEM **POWER 四粗母座**
 PART NO **DP0400010**
 TOLERANCE .X±0.2
 .XX±0.10

ANGLE PROJECTION	UNIT	mm			
	SCALE	2:1		加標尺寸	01/12/2007
	DATE	01/12/2007	REVISION	DESCRIPTION	DATE