


LAYOUT

SPECIFICATIONS:

1. Rating: DC 20V 7.5A Max.
2. Contact: resistance: 30mΩ Max.
3. Insulation Resistance: DC 250V 50MΩ Min.
4. Voltage Withstanding: AC 250V 1Minute.
5. INSERTION FORCE: 4.5kgf Max.  
WITHDRAWAL FORCE: 1.0kgf~4.5kgf Min.

4	護蓋	SPCC T=0.40±0.03MM	TIN	1	
3	接地銅管	BRASS T=0.40±0.03MM	PLATED	1	
2	PIN	BRASS T=0.30±0.03MM	PLATED	4	
1	膠心	PBT+15%GF, UL 94 V-0	PLATED	1	
項次	名稱	材 料	電 鍍	數量	備註


**東莞世華電子有限公司**  
 SHYH HWA ELECTRONICS CO.,LTD.(DONGGUAN)  
 地址: 東莞市塘廈鎮諸佛嶺178工業區  
 TEL: 0769-7910020-1 FAX: 0769-7910210

DRAWN BY		ITEM	POWER 四組母座 +護蓋		ANGLE PROJECTION	UNIT	MM				
CHECKED BY						SCALE	2.5:1				
APPROVED BY		PART NO	DP0400010-A	TOLERANCE	X.XX±0.20	DATE	08/23/2002	REVISION		DESCRIPTION	DATE