

LAYOUT

SPECIFICATIONS:

1. Rating: PIN 1&2: DC 20V 7.5A Max.  
PIN 3: DC 20V 1A Max.
2. Contact: resistance: 30mΩ Max.
3. Insulation Resistance: DC 250V 50MΩ Min.
4. Voltage Withstanding: AC 250V 1Minute.
5. Applicable Wire Size:  
PIN 1&2: AWG #18 Max.  
PIN 3: AWG #24 Max.

TABLE:



A	電鍍
1	亮錫
2	鎳

項次	名稱	材料	電鍍	數量	備註
5	護蓋	SPCC,T=0.40±0.03MM	SEE TABLE	1	
4	接地銅管	BRASS,T=0.40±0.03MM	TIN PLATED	1	
3	粗PIN	BRASS,T=0.30±0.03MM	TIN PLATED	2	
2	細PIN	PHOSPHOR BRONZE T=0.20±0.03MM	TIN PLATED	1	
1	膠心	PBT+15%GF,UL 94 V-0	NONE	1	


**東莞世華電子有限公司**  
 SHYH HWA ELECTRONICS CO.,LTD.(DONGGUAN)  
 地址: 東莞市塘廈鎮諸佛嶺178工業區  
 TEL: 0769-7910020-1 FAX: 0769-7910210

DRAWN BY 陳長江  
 CHECKED BY  
 APPROVED BY

ITEM POWER 二粗一細母座  
 +護蓋  
 PART NO DP0300010-A  
 TOLERANCE  $.X \pm 0.2$   
 $.XX \pm 0.10$

ANGLE PROJECTION  

 UNIT MM  
 SCALE 1:1  

 修訂圖面尺寸公差 09/21/2009  
 DATE 09/21/2009 REVISION DESCRIPTION DATE