



4	14.7L接地片	SL1471202	1	磷銅或鍍銅, T=0.30±0.03MM SILVER PLATED.	
3	3-8P 切溝母銅管 (溝6.3*1.6)	FT1109101	1	BRASS, T=0.40±0.03MM. NICKEL PLATED OR GOLD FLASH PLATED	
2	7P AMP 母膠心	FE0007101	1	PBT+15%GF, UL 94 V-0	
1	1.2*14.0L母PIN (8-9母頭專用)	PI32140XX	7	PHOSPHOR BRONZE, T=0.20±0.03MM PLATING: SEE TABLE	
項目	名稱	料號	數量	規格	備註

ELECTRICAL CHARACTERISTICS:
 RATING: 100V AC 1A MAX or
 12V DC 2A MAX
 INSULATION RESISTANCE:
 50mΩ MIN at 250V DC
 DIELECTRIC STRENGTH:
 250V AC/1 minute

TABLE:

XX	PLATING	05	GOLD PLATED 5u" MIN.
00	NICKEL PLATED.	06	GOLD PLATED 10u" MIN.
01	TIN PLATED.	07	GOLD PLATED 15u" MIN.
02	SILVER PLATED.	08	GOLD PLATED 20u" MIN.
03	GOLD FLASH PLATED.	09	GOLD PLATED 30u" MIN.
04	GOLD PLATED 3u" MIN.	10	GOLD PLATED 50u" MIN.

東莞世華電子有限公司
 SHYH HWA ELECTRONICS CO.,LTD.(DONGGUAN)
 地址: 東莞市塘廈鎮諸佛嶺178工業區
 TEL: 0769-7910020-1 FAX: 0769-7910210

DRAWN BY		ITEM	7P AMP切溝母頭+片 (溝6.3*1.6)		ANGLE PROJECTION	UNIT	MM				
CHECKED BY						SCALE	5:1				
APPROVED BY		PART NO	FJ10701XX-C	TOLERANCE	X.XX±0.20	DATE	09/28/2001	REVISION		DESCRIPTION	DATE