



BUILD OF MATERIAL:

3	3-8P LOCK母銅管	1	FT05091XX	BRASS, T=0.70±0.05MM PLATED:SEE TABLE1	
2	6P 母膠心	1	FE0006001	PBT+15%GF, UL 94 V-0, BLACK	
1	14.0L 母PIN	6	PI30140XX	PHOSPHOR BRONZE, T=0.20±0.03MM PLATING:SEE TABLE2	
項次	名稱	數量	料號	規格	備註

ELECTRICAL CHARACTERISTICS:

RATING: 100V AC 1A MAX or
12V DC 2A MAX
INSULATION RESISTANCE:
50MΩ MIN at 250V DC
DIELECTRIC STRENGTH:
250V AC/1 minute
INSERTION FORCE: 4.5kgf MAX.
WITHDRAWAL FORCE: 5.0kgf~10.0kgf

TABLE1:

XX	PLATING
01	NICKEL PLATED
03	GOLD FLADH PLATED

TABLE2:

XX	PLATING	05	GOLD PLATED 5u" MIN.
00	NICKEL PLATED.	06	GOLD PLATED 10u" MIN.
01	TIN PLATED.	07	GOLD PLATED 15u" MIN.
02	SILVER PLATED.	08	GOLD PLATED 20u" MIN.
03	GOLD FLASH PLATED.	09	GOLD PLATED 30u" MIN.
04	GOLD PLATED 3u" MIN.	10	GOLD PLATED 50u" MIN.

東莞世華電子有限公司
SHYH HWA ELECTRONICS CO.,LTD.(DONGGUAN)
地址:東莞市塘廈鎮諸佛嶺178工業區
TEL:0769-7910020-1 FAX:0769-7910210

DRAWN BY	彭志婷
CHECKED BY	
APPROVED BY	

ITEM	6P LOCK母頭 (15.7L)
PART NO	FL00601XX
TOLERANCE	.X±0.2 .XX±0.10

ANGLE PROJECTION	UNIT	mm		
SCALE	5:1		增加TABLE表	03/23/2012
DATE	03/23/2012	REVISION	DESCRIPTION	DATE